

RESTO

TECHNICAL PRODUCT DATA

RESTO ROOF COAT W.B

a) Product Name	
b) Reference	Resto Roof WB
c) Product Description	A highly durable water borne acrylic coating providing a low sheen, weather resistant finish. Ideally suited for the decoration of exposed concrete and mineral composite roof surfaces.
d) Uses	Ideally suited for the decoration and protection of exposed concrete roof tiles, mineral composite roof surfaces and asbestos sheeting.
e) Pack Sizes	5 & 15 Litres
f) Colour Range	Terracotta, Tile red, Autumn Brown, Tile Brown, Sage Green, Country Green, Grey Stone, Slate Grey, Black.
g) Specific Gravity	1.25 Approx
h) Flash Point	N.A
i) Solids	Approx 50 % by weight. 37 % by Volume
j) Spreading Rate @ D.R.A.T	5 -7 m2 per litre per coat (2 coats recommended)
k) Drying Time	1 – 2 hours @ 20° C 65% RH
l) Overcoating Time	2 - 4 hours @ 20° C 65% RH
m) Lowest Application Temperature	5°C Do not apply in cold, damp conditions
n) Dry Recommended Application Thickness D.R.A.T	55 –75 microns per coat
o) Methods of Application	Brush, roller and spray
p) Recommended Preparation	See Info sheet.
q) Storage Life	At least 1 Year Store upright in a secure frost free place and away from direct heat.
r) Thinner / Cleaner	Thin if required with clean water. Wash equipment immediately after use in water and detergent.
s) Precautions	Protect from frost.
t) Safety	Refer to the appropriate safety data sheet.
u) Volatile Organic Content (VOC)	Approx 50g / litre